GUARDIAN BS 6.8

FASTENER FOR STEEL DECK UP TO 2 X 1,25



	Number	ETA-08/0285 Annex 1:35	
1	Unique identification code of the product-type:	Guardian BS 6.8	
2	Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):	See product label	
3	Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:	Fastening of thermal insulation and waterproofing systems on external roofs to substrates of thin steel deck	
4	Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):	Guardian BV, Grasbeemd 14, 5705 DG Helmond, Netherlands	
		Guardian Fastening System	
5	Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2):	Not relevant	
6	System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:	2+	
7	In case of the declaration of performance concerning a construction product covered by a harmonized standard: - name and identification number of the notified body: - body, system for the assessment/verification of the constancy of performance: - certificate of conformity of the factory production control:	EAD ETA	ucer: Guardian B.V. .guardian.nl 030351-00-0402 08/0285 1071-CPR-1510 ackaging
8	In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued: - name and id- number of the Technical Assessment Body: - harmonized technical specification:	Sintef Building and Infrastructure EAD 030351-00-0402 ETA-08/0285 Sintef Building and Infrastructure 2+ 1071 – CPR – 1510	
	 European Technical Assessment / approval: body, system for the assessment/verification of the constancy of performance: certificate of conformity of the factory production: 		
9	Declared performance		
	Essential characteristics	Performance	Harmonized technical specification
	EAD 030351-00-0402 A2.1 Axial loading test (pull out)	See ETA-08/0285	See ETA-08/0285
	EAD 030351-00-0402 A2.1 Profiled metal decking 0,50mm (280 MPa)	F _{char} 1060 N	See ETA-08/0285
	EAD 030351-00-0402 A2.1 Profiled metal decking 0,60mm (280 MPa)	F _{char} 1310 N	See ETA-08/0285
	EAD 030351-00-0402 A2.1 Profiled metal decking 0,70mm (280 MPa)	F _{char} 1780 N	See ETA-08/0285
	EAD 030351-00-0402 A2.2 Testing of resistance to unwinding	Passed	See ETA-08/0285
	EAD 030351-00-0402 A2.4 Corrosion resistance	30 cycles (2L SO ₂)	See ETA-08/0285

10 Ecology, health and safety information

As per the EC regulation 1907/2006 (REACH) Article 31 a safety data sheet is not required for putting into circulation and placing on the market or using this item. If the item is used as intended and disposed of (disposal or recovery) as per the applicable legislation, the environment is not harmed. This item does not contain any substances that are released under normal conditions or foreseeable conditions of use. There are therefore no registration requirements for substances in this item in the context of Article 7 paragraph 1 of the regulation. Based on our current knowledge this item does not contain any SVHC (Substances of Very High Concern) in concentrations over 0.1 % (w/w) weight by weight as per the candidate list published by the European Chemicals Agency (ECHA).

11 Explanation

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4. Signed for and on behalf of the manufacturer by:

Minh Ta Product Manager

Place and date of issue: Helmond 01/06/2022 305/2011)

(DOP as per EU construction products regulation no.