

BS 6,8 + SP 50 COMBI

Metal pressure plate-screw combi for use in thin profiled steel sheets min. 0.5 mm. Ideal for direct fastening of roofing membranes on sandwichpanels.

- Metal pressure plate \varnothing 50mm, flat, thickness 1.0 mm, star shaped hole
- BS 6,8 steel screw; length 35 mm, \varnothing .6.8 mm, reduced drillpoint
- Tx-25 head
- For use with bitextender ITSU-EXT+BIT-T25-M6S and IT-TS-EXT TS Woodstick
- High-quality, protective coating, 30 cycles
- ETA approval 08/0285
- Note: pull-out test recommended on steel thinner than 0,65 mm



Products

| PRODUCT CODE | \varnothing MM X LENGTH MM | PACKAGING |
|--------------|------------------------------|------------|
| 1514654 | BS-68035 +SP 50 | 250/Bucket |

| PRODUCT CODE | \varnothing MM X LENGTH MM | PACKAGING |
|--------------|------------------------------------|-----------|
| 1412058 | IT-BELT-L, Belt pouch | 1 |
| 1413013 | BIT-T25-TS-EXT BIT M6 forWoodstick | 1 |
| 1413095 | IT-TS-EXT TS, Woodstick | 1 |

Associated products

