

# R 45 (FM APPROVAL)

## Standard tube for fastening of membranes in the overlap

- Modified PP
- Size  $\varnothing$  45 mm
- Length 20mm t/m 730mm
- To combine with a  $\varnothing$  4.8 or 6.1 mm screw
- From length 40 mm till 210 mm, this tube is also available in Large Nose (LN) edition, for the perfect combination with the LBS  $\varnothing$  8,0 mm screw
- ASTL for tapered insulation: see Concrete deck
- Sintef approval 2516
- FM approval



## Products

PRODUCT CODE	$\varnothing$ MM X LENGTH MM	PACKAGING
1412346	R45-020, 45 X 20mm	1000
1412347	R45-040, 45 X 40mm	500
1412348	R45-060, 45 X 60mm	500
1412349	R45-080, 45 X 80mm	500
1412350	R45-090, 45 X 90mm	500
1412351	R45-100, 45 X 100mm	500
1412352	R45-120, 45 X 120mm	500
1412353	R45-150, 45 X 150mm	500
1412354	R45-180, 45 X 180mm	500
1412355	R45-210, 45 X 210mm	500
1412356	R45-240, 45 X 240mm	500
1412357	R45-270, 45 X 270mm	250
1412358	R45-300, 45 X 300mm	250
1412359	R45-330, 45 X 330mm	250
1481704	R45-430, 45 X 430mm	250
1481705	R45-530, 45 X 530mm	250
1481706	R45-630, 45 X 630mm	200
1481708	R45-730, 45 X 730mm	200

## Associated products



### **BS 4,8 (FM Approval)**

For use with BIT-T25  
Torx-25 head  
Ø 4,8 mm



### **CS 6,1 (FM Approval)**

Pre-drill: 5,0 mm.  
In hard concrete 5,2 mm  
Torx-25 head  
Hi-lo thread



### **LBS 6,0**

Torx-25 head  
S-point  
Length: 60 to 240 mm



### **PS 4,8**

For use with BIT-T25  
Torx-25 head  
Ø 4,8 mm