

# RB 48 (FM APPROVAL)

High performance tube (barbed) for fastening of synthetic membranes in the overlap, for a higher design load

- Modified PP
- Size  $\varnothing$  48 mm
- Length: 20 t/m 330 mm
- To combine with a  $\varnothing$  4.8 or 6.1 mm screw
- Sintef approval 2516
- ETA approval 08/0285
- FM approval



## Producten

ARTIKELCODE	$\varnothing$ MM X LENGTE MM	VERPAKKING
1412587	RB48-020, 48 X 20mm	1500
1412588	RB48-040, 48 X 40mm	1500
1412589	RB48-060, 48 X 60mm	1500
1412590	RB48-080, 48 X 80mm	1500
1412591	RB48-090, 48 X 90mm	1500
1412592	RB48-100, 48 X 100mm	1000
1412593	RB48-120, 48 X 120mm	1000
1412595	RB48-150, 48 X 150mm	750
1412597	RB48-180, 48 X 180mm	500
1412599	RB48-210, 48 X 210mm	500
1412601	RB48-240, 48 X 240mm	250
1412603	RB48-270, 48 X 270mm	250
1412604	RB48-300, 48 X 300mm	250
1412605	RB48-330, 48 X 330mm	250

## Associated products



### **BS 4,8 (FM Approval)**

For use with BIT-T25  
Tx-25 head  
Ø 4,8 mm



### **CS 6,1 (FM Approval)**

TX 25 head  
Hi-lo thread  
Length: from 28 to 280 mm



### **TS 5,2**

TX 25 head  
S-Point  
Length: 20 to 120 mm



### **LBS 6,0**

TX 25 head  
S-Point  
Length: 60 to 240 mm



### **PS 4,8**

For use with BIT-T25  
TX 25 head  
Ø 4,8 mm



### **BS 6,1**

For use with BIT-T25  
TX 25 head  
Ø 6,1 mm