

R 75 (FM APPROVAL)

Standard tube for fastening of thermal insulation boards or base layer

- Modified PP
- Size \varnothing 75 mm
- Length: 20 t/m 330 mm
- To combine with a \varnothing 4.8 or 6.1 mm screw
- ASTL for tapered insulation see Concrete deck
- ETA approval 08/0285
- Sintef approval 2516
- FM approval



Products

PRODUCT CODE	\varnothing MM X LENGTH MM	PACKAGING
1412495	R75-020, 75 X 20mm	1000
1412496	R75-040, 75 X 40mm	1000
1412497	R75-060, 75 X 60mm	1000
1412498	R75-080, 75 X 80mm	750
1412499	R75-090, 75 X 90mm	750
1412500	R75-100, 75 X 100mm	500
1412501	R75-120, 75 X 120mm	500
1412503	R75-150, 75 X 150mm	500
1412505	R75-180, 75 X 180mm	250
1412507	R75-210, 75 X 210mm	250
1412509	R75-240, 75 X 240mm	250
1412510	R75-270, 75 X 270mm	250
1412511	R75-300, 75 X 300mm	250
1412512	R75-330, 75 X 330mm	250

Associated products



BS 4,8 (FM Approval)

For use with BIT-T25
Torx-25 head
Ø 4,8 mm



CS 6,1 (FM Approval)

Pre-drill: 5,0 mm.
In hard concrete 5,2 mm
Torx-25 head
Hi-lo thread



LBS 6,0

Torx-25 head
S-point
Length: 60 to 240 mm



PS 4,8

For use with BIT-T25
Torx-25 head
Ø 4,8 mm