

R50

Standard tube for fastening of membranes in the overlap

- To combine with a $\varnothing$ 4,8 to 6,8 mm screw
- Length 20mm to 730mm
- Modified PP
- Size $\varnothing$ 50 mm
- From length 40 mm till 210 mm, this tube is also available in Large Nose (LN) edition, for the perfect combination with the LBS $\varnothing$ 8,0 mm screw
- ASTL for tapered insulation: see Concrete deck
- ETA approval 08/0285
- Sintef approval 2516



Products

PRODUCT CODE	$\varnothing$ MM X LENGTH MM	PACKAGING
1715409	R50-020, 50 X 20mm	1500
1715410	R50-040, 50 X 40mm	1500
1715411	R50-060, 50 X 60mm	1500
1715412	R50-080, 50 X 80mm	1500
1715413	R50-090, 50 X 90mm	1500
1715432	R50-100, 50 X 100mm	1000
1715433	R50-120, 50 X 120mm	1000
1715434	R50-150, 50 X 150mm	750
1715435	R50-180, 50 X 180mm	500
1715436	R50-210, 50 X 210mm	500
1715437	R50-240, 50 X 240mm	250
1715438	R50-270, 50 X 270mm	250
1715439	R50-300, 50 X 300mm	250
1715440	R50-330, 50 X 330mm	250
1715441	R50-430, 50 X 430mm	250
1715442	R50-530, 50 X 530mm	250
1715445	R50-630, 50 X 630mm	250
1715447	R50-730, 50 X 730mm	250

Associated products



BS 4,8 (FM Approval)

For use with BIT-T25
TX 25 head
Ø 4,8 mm



CS 6,1 (FM Approval)

Pre-drill: Ø 5,0 mm. In hard
concrete 5,2 mm
TX 25 head
Hi-lo thread



LBS 6,0

TX 25 head
S-Point
Length: 60 to 240 mm



PS 4,8

For use with BIT-T25
TX 25 head
Ø 4,8 mm